STEPPEDHEX TECHNOLOGY

Innovative Engraving Technology from Zecher





Zecher GmbH Görlitzer Straße 2 • 33098 Paderborn • Germany Tel. +49 5251 1746-0 • contact@zecher.com www.zecher.com








INNOVATIVE ENGRAVING TECHNOLOGY

The SteppedHex technology, protected by a German utility model, is characterised by its unique, specially staggered cell geometry. The engraving is based on the familiar 60° angle, with the connection of just three consecutive conventional cells. In order to let you take full advantage of this open engraving system, we have optimised the levels of resolution (L/cm) with respect to the corresponding volume.


If you have any further questions, please consult with the Zecher team. We will be happy to advise you, and act jointly to find the best specification for your requirements.

Weiß/Fläche White/Solid Area


Weiß H.I.T. 60° White H.I.T. 60°



400 L/cm: 4.0 cm3/m2 Hex. 60°: 1% + 2% tonal value, 60 L/cm



580L/cm; 4,0 cm3/m2 SteppedHex: 1 % + 2 % tonal value, 60 L/cm




Line Work/Solid Area

Weiß/Flāche White/Solid Area

Weiß/Fläche White/Solid Area

SteppedHex 60°



all inking systems. • The transfer of white, lacquer, gold or silver in the course of printing and with special coating media is especially uniform

and homogeneous.

160 Ycm 400 hi

120,120 Year 14/00E,025

TECHNICAL BENEFITS

loss of volume.

• Higher resolution, without any significant

Smooth running of your doctor blade

• The special staggered engraving lets you

achieve optimum printing-nip dimensions.

• The customised levels of resolution (L/cm) and the specific staggered structure provide

you with defined, optimal support for the

• The ink transfer, which is benefited by the

shape of the cell, permits application with

print format, in addition to the combination area, even in the higher-resolution raster.

on the surface of the anilox roller.

• The unique cellular form improves

evacuation and cleaning.



+ 80 L/cm

100,120,140 Ucm 250,350,350 lpi

120, 140, 160, 180 Uan 300, 350, 400, 450 bi

